

VECTOR® HE 19 MT



MHS 700



MHS 1100



MHD 1100



MHS 2200



MHD 2200

| | | | | | | | | | |
|----------------------------|-------------------------------|---------------------|-------------------|------------|------------|------------|------------|------------|---------|
| Type | <i>Version</i> | Multi Temperature | | | | | | | |
| | <i>Variant</i> | Road & Standby | | | | | | | |
| | <i>Noise insulation</i> | Standard | | | | | | | |
| | <i>Technology</i> | E-Drive | | | | | | | |
| Cooling capacity | <i>Diesel - High Speed</i> | 0°C/30°C | host unit | Main evap | MHS 2200 | MHS1100 | MHS 700 | MHD2200 | MHD1100 |
| | | -10°C/30°C | 17765 W | 16830 W | 13100 W | 10740 W | 7865 W | 15670 W | 11260 W |
| | | -20°C/30°C | 13495 W | 13050 W | 10380 W | 8720 W | 6555 W | 12275 W | 8860 W |
| | <i>Standby - 400V/3/50 Hz</i> | 0°C/30°C | 9225 W | 9270 W | 7660 W | 6695 W | 5250 W | 8875 W | 6460 W |
| | | -10°C/30°C | 16325 W | 14890 W | 12280 W | 10060 W | 7375 W | 13570 W | 10465 W |
| | | -20°C/30°C | 12460 W | 11590 W | 9780 W | 8160 W | 6120 W | 10800 W | 8430 W |
| ATP compliant | | 8595 W | 8290 W | 7275 W | 6260 W | 4865 W | 8025 W | 6395 W | |
| Heating capacity | <i>Diesel</i> | 9200 W | 9200 W | 9600 W | 5400 W | 3300 W | 9600 W | 5400 W | |
| | <i>Standby - 400V/3/50 Hz</i> | 8300 W | 4500 W | 9600 W | 5400 W | 3300 W | 9600 W | 5400 W | |
| Airflow | <i>ISO 5801</i> | - | 5240 m3/hr | 3430 m3/hr | 1910 m3/hr | 1020 m3/hr | 3470 m3/hr | 2220 m3/hr | |
| | | Standard | Silent | | | | | | |
| Weight | | 825 kg | 845 kg (TBC) | 22 kg | 33 kg | 62 kg | 40 kg | 71 kg | |
| | | | | | | | | | |
| Dimensions | <i>Height</i> | 2227 mm | - | 200 mm | 200 mm | 167 mm | 167 mm | 167 mm | |
| | <i>Width</i> | 2050 mm | - | 700 mm | 1044 mm | 2150 mm | 1044 mm | 2150 mm | |
| | <i>Depth</i> | 430 mm | - | 752 mm | 752 mm | 944 mm | 944 mm | 944 mm | |
| Sound emission | <i>Diesel - High speed</i> | <i>Power Lwa</i> | Standard | Silent | | | | | |
| | | <i>Pressure</i> | 100 dB | 98 dB | | | | | |
| | <i>Diesel - Low speed</i> | <i>Pressure</i> | 69 dB | 66 dB | | | | | |
| | | <i>Pressure</i> | 63 dB | 60 dB | | | | | |
| <i>Standby 400/3/50 Hz</i> | <i>Pressure</i> | 60 dB | 58 dB | | | | | | |
| Components | <i>Engine</i> | <i>Displacement</i> | 2200 cc | | | | | | |
| | | <i># cylinders</i> | 4 | | | | | | |
| | <i>Compressor</i> | <i>Techno</i> | Scroll economized | | | | | | |
| | | <i>Model</i> | ZF22 | | | | | | |
| <i>Controls</i> | | APX | | | | | | | |
| Refrigerant | <i>Refrigerant</i> | <i>Type</i> | R452A | | | | | | |
| | | <i>Charge</i> | 7,5 | | | | | | |