

SX-160DG/SX-120DG 数控袋装卷簧机

SX-160DG/ SX-120DG DIGITAL POCKET SPRING MACHINE

- ★ 无纺布纠偏系统
Fabric Correction System
- ★ 160/120只每分钟
160/120 Springs per min
- ★ 人机界面内置智能弹簧成型系统
HMI inserted with intelligent caculation system
- ★ 单钢丝
Single Wire



SX-3 切断机
SX-3 CUTTING MACHINE

■ 专利产品 仿冒必究
Patent Products All Rights Reserved

■ 已通过CE认证
CE Certified

技术参数

弹簧类型	中凸型或直筒型
生产效率	160/120只每分钟
弹簧中径	Φ45-Φ70MM Φ37-Φ50MM
钢丝直径	Φ1.4-Φ2.3MM (<Φ1.4MM 可定制)
装袋后高度	70-220MM (<70或>220MM可定制)
无纺布宽度	≤ 650MM
无纺布厚度	≥60G/M ²
无纺布直径	≤1M
主功率	30KVA
气源需求	10 M ³ /H
重量	3340KG
电压要求	380V,3相,50-60HZ (可选: 415V-480V, 220V)

Technical Data

Spring Type	Barrel or Cylindrical
Capacity	160/120 Springs per min
Spring Waist ext Dia	Φ45-Φ70MM Φ37-Φ50MM
Steel Wire Gauge	Φ1.4-Φ2.3MM (<Φ1.4MM on request)
Pocket Height	70-220MM (<70 or >220MM on request)
Fabric Width	≤ 650MM
Fabric Thickness	≥60G/M ²
Fabric Diameter	≤1M
Main Drive Power	30KVA
Air Consumption	10 M ³ /H
Weight	3340KG
Power Requirement	380V,3 Phase,50-60HZ (Option: 415V-480V, 220V)

产品图片和参数仅为参考，一切以实物为准，最终解释权归本厂所有，敬请事先了解
Subject to changes without notice.
The machine will be set for one spring type only from its working range. Each additional modification of the actual coil specification (Dia, Wire, turns, height etc.) may request additional tools.

