



LINER side swathers <sup>1</sup>		1900	1800 TWIN <sup>2</sup>	1700 TWIN <sup>2</sup>	1700	1600 TWIN <sup>2</sup>	1600	800 TWIN <sup>2</sup>	700 TWIN <sup>2</sup>	500 PROFIL	450	420	370	320	500 T	450 T
<b>Dual-rotor swathers</b>																
Mounting								Swinging draw-bar/hitch	Swinging draw-bar/hitch	Three-point	Three-point/swiv-elling head	Three-point/swiv-elling head	Three-point/swiv-elling head	Three-point/swiv-elling head	Swinging draw-bar/hitch	Swinging draw-bar/hitch
Hitch category		Cat. II	Cat. II	Cat. II	Cat. II	Cat. II	Cat. II	–	–	Cat. II	Cat. I + II	Cat. I + II	Cat. I + II	Cat. I + II	–	–
Working width	m (DIN)	8.05	7.45–8.40	6.70–7.85	6.60	6.20–6.90	6.20	4.00–7.50	3.50–6.30	4.80	4.50	4.20	3.70	3.20	4.80	4.50
Transport width																
With tine arms mounted	m	2.99	2.99	2.89/2.99	2.89/2.99	2.89/2.99	2.89/2.99	3.60	3.00	3.80 <sup>3</sup>	3.50 <sup>3</sup>	3.20 <sup>3</sup>	2.98 <sup>3</sup>	2.80	3.80 <sup>3</sup>	3.50 <sup>3</sup>
With tine arms removed	m	–	–	–	–	–	–	2.42	2.42	2.40	2.30	2.00	1.53 <sup>4</sup> /1.75	2.25 <sup>4</sup> /2.45	2.50	2.20
Transport height																
With tine arms mounted	m	3.99	3.99	3.99	3.99	3.64	3.79	–	–	–	–	–	–	1.52	–	–
With tine arms removed	m	–	–	–	3.67	–	–	–	–	2.45	2.45	2.35	2.15	2.15	2.45	2.45
Parking length (transport position)	m	9.64	9.19	8.66	8.66	8.25	8.25	8.55	8.00	3.30	4.10	3.80	2.55	2.43	4.40	5.25
Weight approx.	kg	2590	2480	2220	2080	1950	1810	1620	1440	805	650	560	450	380	785	660
Rotors	Qty	2	2	2	2	2	2	2	2	1	1	1	1	1	1	1
Rotor diameter	m	3.80	3.50	3.20	3.20	2.90	2.90	3.50	2.90	3.80	3.50	3.20	2.90	2.65	3.80	3.50
Tine arms per rotor	Qty	14	12	12	12	11	11	12	11	14	12	12	11	8	14	12
Dual tines per arm set	Qty	4	4	4	4	4	4	4	4	4	4	4	3 (4 ◊)	3	4	4
Tine diameter	mm	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.50	9.00	9.00	9.00	9.00	9.50	9.00
PROFIX tine arm bracket		●	●	●	●	–	–	●	●	●	●	●	–	–	●	●
Swath-laying position		left	left	left	left	left	left	left	left	left	left	left	left	left	left	left
Two-wheel rotor chassis		–	–	–	–	–	–	–	–	–	–	–	●	●	–	–
Four-wheel rotor chassis		●	●	●	●	●	●	●	●	●	●	●	●	◊	●	●
Six-wheel rotor chassis		◊	◊	◊	◊	–	–	–	–	◊	–	–	–	–	–	–
<b>Tires</b>																
Rotor chassis	16x6.50-8 10 PR	2x4 (2x6 ◊)	2x4 (2x6 ◊)	2x4 (2x6 ◊)	2x4 (2x6 ◊)	2x4	2x4	–	–	2x4 (2x6 ◊)	4	4	2 (4 ◊)	2 (4 ◊)	–	–
	18x8.50-8 6 PR	–	–	–	–	–	–	2x4	2x4	–	–	–	–	–	4	4
	10.00/75-15.3 10 PR	–	●	●	●	●	●	–	–	–	–	–	–	–	–	–
Main frame	380 /55 - 17	●	●	–	–	–	–	–	–	–	–	–	–	–	–	–
	340/55-16	–	◊	◊	◊	◊	◊	–	–	–	–	–	–	–	–	–
Fully floating suspension		●	●	●	●	●	●	● <sup>5</sup>	● <sup>5</sup>	●	–	–	–	–	–	–
<b>Drive systems</b>																
PTO shaft speed	rpm	540	540	540	540	540	540	540	540	540	540	540	540	540	540	540
Single wide-angle PTO drive shaft		●	●	●	●	●	●	●	●	–	–	–	–	–	●	●
<b>Convenience</b>																
Spare wheel 16x6.50-8 10 PR		◊	◊	◊	◊	◊	◊	–	–	–	–	–	–	–	–	–
Spare wheel 18x8.50-8 6 PR		–	–	–	–	–	–	◊	◊	–	–	–	–	–	–	–
Wheel weights		◊	◊	◊	◊	◊	◊	–	–	–	–	–	–	–	–	–
Double wide-angle PTO drive shaft		–	–	–	–	–	–	◊	◊	–	–	–	–	–	–	–
TWIN function		–	●	●	–	●	–	●	●	–	–	–	–	–	–	–
Guide wheel		–	–	–	–	–	–	◊	◊	–	◊	◊	◊	–	◊	◊
Hydraulic folding of swath guard		◊	◊	◊	◊	◊ <sup>7</sup>	◊ <sup>7</sup>	◊	◊	◊	◊	◊	–	–	◊	◊
Hydraulic rotor height adjustment		–	–	–	◊	◊	◊	–	–	◊	◊	◊	–	–	–	–
Warning sign		–	–	–	–	–	–	–	–	◊	◊	◊	◊	◊	◊	◊
Warning sign with illumination		●	●	●	●	●	●	●	●	◊	◊	◊	◊	◊	◊	◊
Parallelogram drawbar		–	–	–	–	–	–	●	◊	–	–	–	–	–	◊	◊
Hydraulic spool valves		1xsa (+ 1xsa <sup>8</sup> )	1xsa (+ 1xsa <sup>8</sup> )	1xsa (+ 1xsa <sup>8</sup> )	1xsa (+ 1xsa <sup>8</sup> )	1xsa	1xsa	1xsa	1xsa	–	–	–	–	–	1xsa	1xsa
		1xda	1xda	1xda	1xda	(1xda <sup>7</sup> )	(1xda <sup>7</sup> )	1xda	1xda	(2xda <sup>6,8</sup> )	(2xda <sup>6,8</sup> )	(2xda <sup>6,8</sup> )	–	–	(1xda <sup>6</sup> )	(1xda <sup>6</sup> )

- 1 Swath former cloth guard
- 2 TWIN function (option) with additional swath guard for front rotors

- 3 Swath guard and protective frame folded
- 4 LINER 370 and 320 with single axle
- 5 Rear only

- 6 Hydraulic folding of swath guard
- 7 Hydraulic swath guard adjustment
- 8 Hydraulic rotor height adjustment

● Standard ◊ Option ◻ Available – Not available

CLAAS continually develops its products to meet customer requirements. This means that all products are subject to change without notice. All descriptions and specifications in this brochure should be considered approximate and may include optional equipment that is not part of the standard specifications. This brochure is designed for worldwide use. Please refer to your nearest CLAAS dealer and their price list for local specification details. Some protective panels may have been removed to present the function more clearly in photographs. To avoid any risks, you should never remove these protective panels yourself. In this context, please refer to the relevant instructions in the operator's manual.

● Standard ◊ Option ◻ Available – Not available

LINER central swathers		4000	3600	3100	2900	2800	2700	2600
		<b>Four-rotor swathers</b>		<b>Dual-rotor swathers</b>				
Hitch category		Cat. III	Cat. II	Cat. II	Cat. II	Cat. II	Cat. II	Cat. II
Working width	m (DIN)	12.20–15.00	9.90–12.50	8.70–10.00	8.00–9.00	7.40–8.20	6.80–7.40	6.20–6.80
Swath width <sup>1 ca.</sup>	m	1.50–2.60	1.20–2.30	1.50–2.60	1.20–2.40	1.20–2.20	1.20–2.00	1.10–1.80
Transport width								
With tine arms mounted	m	3.00	3.00	2.97	2.97	2.97	2.97	2.97
Transport height								
With tine arms mounted	m	3.99	3.99 <sup>2</sup>	4.46	3.99	3.99	3.99	3.99
With tine arms removed	m	3.57	3.40	3.75	3.72	3.47	3.38	3.18
Parking length (transport position)	m	10.16	8.70	6.92	6.53	6.53	5.87	5.87
Rotors	Qty	4	4	2	2	2	2	2
Rotor diameter	m	3.80	3.30	4.20	3.80	3.50	3.20	2.90
Tine arms per rotor	Qty	14	12	14	14	12	12	11
Dual tines per arm set	Qty	4	4	5	4	4	4	4
Tine diameter	mm	9.5	9.5	9.5	9.5	9.5	9	9
PROFIX tine arm bracket		●	●	●	●	●	●	–
Swath-laying position		Centre	Centre	Centre	Centre	Centre	Centre	Centre
Four-wheel rotor chassis		● <sup>3</sup>	●	–	● <sup>3</sup>	● <sup>3</sup>	●	●
Six-wheel rotor chassis		○ <sup>4</sup>	–	● <sup>3</sup>	○	○	○	–
Fully floating suspension		●	●	●	●	●	●	●
<b>Drive systems</b>								
PTO shaft speed	rpm	540	540	540	540	540	540	540
Single wide-angle PTO drive shaft		●	●	●	●	●	●	●
<b>Tyres</b>								
Rotor chassis								
16×6.50-8 10 PR		4×4	4×4	2×6	2×4	2×4	2×4	2×4
Main frame								
10.00/75-15.3 10 PR		–	–	–	–	2	2	2
500/55-20		–	○	–	–	–	–	–
620/40 R 22.5		2	○	–	–	–	–	–
380 /55 - 17		–	2	2	2	○	–	–
Weight approx.	kg	5480	4600	2880	2250	2050	1900	1600
<b>Convenience</b>								
Spare wheel 16×6.50-8 10 PR		○	○	○	○	○	○	○
Wheel weights		–	–	●	○	○	○	–
Single-rotor lifting function (three-way valve)		–	–	○	○	○	○	○
Electrohydraulic individual rotor lift		●	●	○	○	○	–	–
Electrohydraulic rotor height adjustment		○	○	○	○	○	–	–
LED working lights		○	○	–	–	–	–	–
		–	1×sa	1×sa	1×sa	1×sa	1×sa	1×sa
Hydraulic spool valves		1×sa + fR or LS	1×sa + fR or LS	1×da	1×da	1×da	–	–

- 1 Depending on forage conditions and engine speed
- 2 For tyre variant 500/55-20
- 3 Front lateral suspension
- 4 For rear pair of rotors

● Standard ○ Option □ Available – Not available



Ensuring a better **harvest.**

CLAAS UK  
Saxham  
Bury St. Edmunds  
Suffolk  
IP28 6QZ  
Tel 01284 763100  
claas.co.uk  
info-uk@claas.com

365FarmNet enables you to manage your entire agricultural business by means of a single, non-proprietary software solution. Interfaces to intelligent applications created by partners in the agricultural sector offer expert support for your business 365 days a year. CLAAS is a 365FarmNet partner.

