

		EXTREME 1		
	UOM	HTI	HTR	HTC
BALE SIZE				
Diameter	<i>m</i>	0,5-1,65 / 1,8		
Width	<i>m</i>	1,2		
PICK-UP				
Pickup width	<i>m</i>	2,2		
Number of tine bars	<i>n°</i>	4		
Pivoting wheels		Standard		
Crop guide plate		Standard	-	-
Crop guide tine		-	Standard	Standard
Crop guide roller		Optional extra		
BALING CHAMBER				
Belts	<i>type</i>	Stapled		
n° of belts	<i>n°</i>	6		
Bale ejector		Optional extra		
FEEDING				
Cutting length	<i>mm</i>	-	-	77
Knife protection		Spring		
Rotor shut-off		Standard		
Drop floor		-		
BINDING				
Net		Standard		
Twine		Optional extra		
Twine/net		Optional extra		
Plastic film binding		Optional extra		
CONTROL				
Mechanical		Standard		
ICON (electronic)		-		
LUBRICATION				
Automatic oiling		Standard		
Automatic oiling rotary pump		-		
Manual greasing		Standard		
Centralized greasing		-		
Progressive manual greasing		-		
Progressive automatic greasing		-		
TYRES				
400/60 - 15.5		Standard		
19.0/45 - 17		Optional extra		
550/45 - 22.5		-		
Weight	<i>kg</i>	2850	3100	3260

EXTREME 2				EXTREME 3		
HTI	HTR	HTC	HTU	HTR	HTC	HTU
	0,5-1,65 / 1,8			0,5-1,65		
	1,2			1,2		
	2,2			2,2		
	4			4		
	Standard			Optional		
Standard	-	-	-	-	-	-
-	Standard	Standard	Standard	-		
	Optional extra			Standard		
	Endless			Endless		
	6			4		
	Optional extra			Optional extra		
-	-	77	44	-	77	44
	Molla			Molla		
	Standard			-		
	Standard			Standard		
	Standard			Standard		
	Optional extra			Optional extra		
	Optional extra			Optional extra		
	Optional extra			Optional extra		
	-			-		
	Standard*			Standard*		
	Standard			-		
	-			Standard		
	-			-		
	-			Standard		
	Standard			-		
	Optional extra			Optional		
	Standard			Standard		
	Optional extra			Optional extra		
	Optional extra			Optional extra		
2940	3300	3520	3550	3470	3550	3657

***ISOBUS terminal in the ISOTRONIC version**