

# ROAD FORCE® WALKAWAY™

Industry's fastest diagnostic wheel balancer



Give your customers that "new car ride"



Solve vibration problems



Automatic wheel measurements



Error-proof CenteringCheck®



WalkAway™ inflation saves minutes



11.5 cm more compact than previous models



# ROAD FORCE® WALKAWAY™ SPECIFICATIONS



RFW30E shown

|                                  |                                                   |
|----------------------------------|---------------------------------------------------|
| Power requirements               | 196-253V, 10 amp, 50/60 Hz, 1 ph NEMA L6-20P      |
| Air supply requirements          | 7-12 bar (100-175 psi)                            |
| Approximate air consumption      | 113 Liters/Minute (4 CFM)                         |
| Internet recommendations         | Hardwire or Wireless add on, 10+ mbps up and down |
| Roller force                     | Variable up to 567 kg (1,250 lbs)                 |
| Rim width range                  | 38 mm to 521 mm (1.5 in to 20.5 in)               |
| Rim diameter range               | 254 mm to 762 mm (10 in to 30 in)*                |
| ALU                              | 356 mm to 1016 mm (14 in to 40 in)*               |
| Max. tyre diameter               | 1016 mm (40 in)                                   |
| Max. tyre width                  | 508 mm (20 in)                                    |
| Max. tyre weight                 | 79 kg (175 lbs)                                   |
| Radial & lateral runout accuracy | 0.051 mm (0.002 in)                               |
| Imbalance resolution             | ± 0.28 g (0.01 oz)                                |
| Placement accuracy               | 512 positions, ± 0.35°                            |
| Balancing speed                  | 300 rpm                                           |
| Motor                            | Programmable drive system and DC motor            |
| Usable power cord length         | ~ 3505 mm (138 in.)                               |

\* Extreme wheel sizes may require manual data entry.

| RFW                | RFW30E | RFW20E | RFW10E | RFW00E |
|--------------------|--------|--------|--------|--------|
| Wheel Lift System  | ✓      |        | ✓      |        |
| Speedclamp® System | ✓      | ✓      |        |        |

## Your Hunter distributor is ready to help

- ✂ Receive same- or next-day service
- 📞 Get a free quote or on-site demo
- 🎓 Register for training courses
- 📖 General information and questions



Contact your  
local distributor

[hunter.com/contact](https://hunter.com/contact)



Because of continuing technological advances, specifications, models and options are subject to change without notice.

HunterNet, Automatic Centering Check, BullsEye, SpeedClamp, SmartWeight, Smartspot, TruWeight, TPMSSpecs, and HammerHead are registered trademarks of Hunter Engineering Company.

Revolution and WalkAway are trademarks of Hunter Engineering Company.

0126AH

Copyright © 2026, Hunter Engineering Company

**HUNTER**  
Engineering Company

[www.hunter.com](https://www.hunter.com)

11250 Hunter Drive, Bridgeton, MO 63044, USA

Tel: 1-314-731-3020, Fax: 1-314-731-0132

Email: [international@hunter.com](mailto:international@hunter.com)

Form BB08321-05, 01/26